



TRAD Barrelrack (uni, duplo and tetra)

(225L-300L-400L-500L-600L)

- Can be stacked up to 6 tiers high.
- Can be perfectly transported and handled with a single fork from the center of the barrelrack.
- Preserves the image of the traditional staggered stacking, eliminating the classic wedges.

◀ TECHNICAL CHARACTERISTICS (225L)

Exterior dimensions (length x width x height)

1305 x 595 x 260 mm.

Weight

17 Kg/Unit.

Others

Fixed or with wheels.



- Manufactured in high-quality steel and welded with high-fusion wire.
- Epoxy Paint in any colour from the RAL colour chart.
- Galvanized or bichromated.
- Degreased, phosphate-coated and mineralized water treatment.
- 300-400 hrs resistance in a saline fog.



- ☞ To stack barrels, with an avant-garde, daring and functional design.
- ☞ Stacking capacity of more than 6 heights, reducing the total stacking size.



- ☞ There is no physical contact between the iron and the barrel, a rubber profile covers it avoiding damage to the wood and avoiding slipping between the support and the barrel.



- ☞ Ideal for preserving the image of traditional stacking by eliminating the classic wedges, adding stability and safety.



- ☞ Prevents occupational risks due to its reduced movement (it can be transported and handled perfectly with a single fork from the center of the barrel rack).
- ☞ The racking and washing work in the cellar is more efficient due to its characteristics, the lower part of the barrels is completely free to allow the entry and exit of the washing and waste collection elements without uncontrolled spills.
- ☞ The barrel rack allows the incorporation of wheels to facilitate the rotation of the barrel on the same support.

